

Typesetting Data of Koopmann Druck

Supported DTP programs:

Mac

Adobe Acrobat (PDF)
Quark XPress (QXD)
Adobe InDesign (INDD, PDF)
Adobe Illustrator (AI, EPS)
Adobe Photoshop (PSD, TIFF)
Macromedia Freehand (FH, EPS)

PC

Adobe Acrobat (PDF)
Quark XPress (QXD)
Adobe InDesign (INDD, PDF)
Adobe Illustrator (AI, EPS)
Adobe Photoshop (PSD, TIFF)
Corel PhotoPaint (CPT, PSD, TIFF)
Corel Draw (CDR, EPS)
MS Word & Excel (DOC, XLS)

Note: Please deliver documents from other applications in the form of printable PDF files. To help you do so, we will gladly place our distiller settings at your disposal. You can obtain these settings from us or download them on the internet at www.koopmann.info/daten/distiller_koopmann_joboptions.zip. Likewise, you can also send us PostScript files (ps or prn) with embedded typefaces or EPS files (typefaces converted into paths/curves, page format defined). Please create Quark XPress documents without base line grids!

Typefaces: Please deliver the typefaces too or convert them into paths/curves (with Corel Draw, Adobe Illustrator and Freehand) or embed the typefaces in the PostScript/PDF files.

Images:

File formats:	TIFF with LZW compression, EPS uncompressed (no JPEG compression)
Resolution:	300 dpi at positioning 1:1 (100%) size increases and reductions accordingly (e.g. 450 dpi at 150%, 150 dpi at 50%). Do not use RGB images with 72 dpi (bitmap, JPEG, GIF from the Internet)! 1 bit line image/scanned text with 1200 dpi.
Colour depths:	For black/white greyscale images, 8 bit or for colour images CMYK, 32 bit. No RGB images (24 bit), no indexed colours!
Colour separation:	CMYK= standard for print preparations – Europe (Photoshop)
Printing colours:	Euroscale coated
Tonal value increase:	Standard 10 %
Separation type:	GCR
Black structure:	medium
Max. black:	100 %
Total colour application:	350 %
Subcolour addition:	0 %

Logos: Vector EPS (scalable) or TIFF with 1200 dpi. True colours or CMYK Euroscale, no RGB!

Your contact at Koopmann Druck for data-related further inquiries:
Oliver Gawryluk, tel. +49 (0)4 21 56 90 5-14, info@koopmann.de